






Suitable • Limited Suitability



Orange M5YX	Red M2YX	Red M7YX	Red M1PX	Violet M2RX
6	7	7-8	7-8	6-7
6	5	4-5	5	5
4-5	4-5	4-5	5	5
5	4-5	4-5	3-4	5
5	4-5	4-5	5	-5
5	4-5	4-5	5	5
3-4	4-5	4-5	5	5
	4	4	5	4-5
1-2				
1-2	•	•	•	

arrot Green MY	X German Blue MRX	Brown MYX	Brown MRX
And the second s			
The state of the s			
5-6	6-7	3-4	5-6
5	5	5	5
4-5	4-5	4-5	5
4-5	4-5	4-5	4-5
4-5	4-5	4-5	4-5
4-5	4-5	4-5	4-5
4	4	4	4
			1
4	4	4	4
4	•	•	•



Textile Printing by MulticronX™ pigment emultions

.

Characteristics:

- Consistent Quality.
- Colour Robustness.
- Radiant and Special Shades.
- Suitability for all fibers and blends.
- Satisfying varied fastness properties.

Advantage of MulticronX™ pigment emultions

- Superior color yield.
- No Screen chock-up.
- · Fineness in printing.
- Good levelling in large coverage.
- Comfortable handling of printed goods.
- Good flow property.

Guideline for stock paste preparation (Aqueous system)

Water	86.3 - 79.7	parts
Binder	12 -18	parts
Thickner	1.5 -1.8	parts
Liquer Ammonia	0.2 - 0.5	parts
Total	100	parts

Guideline for print paste preparation

MulticronX™	X	parts
Stock Paste	Y	parts
Fixer	0.5 - 2.0	parts
Total	100	parts

Process

Print on well prepared textile substrate.

Dry at 100°C for 3-5 mins.

Fixation at 150°C for 5 mins. / 170°C for 3 mins.

Notes

Amount of Binder, Thickener and Fixer are variables that depend on fabric, design, colour and fastness requirements.







Manufacturer & Exporter of Pigment Emulsions, Dyes & Chemicals

A-224, Anand Tenaments, Opp. Smruti Mandir, Ghodasar, Ahmedabad-380050
Tel.: +91 79 2589 0218 • Cell: +91 99246 40218 • Email: maltichemcorp@gmail.com